		Average Guidelines
Engine		N/A (EV) / V6 or V8
	Fuel delivery	Direct injection /SPFI / direct injection FFV / Hybrid
	Displacment	5.3 L /5.7L/3.3L/
	Compression ratio	11.1/ 10.2/12.1/
	·	AWD / Rear wheel drive
	Horse power	Hybrid powertrain provides increaed power / 260 - 400 bhp @5600rpm /
	Torque	Hybrid powertrain provides increased torque / 383 ft-Ib@4100 /
	Alternator	250amp / 220 amp / 220 amp DC-DC converter
	Battery	Primary for vehicle operation / Auxiliary for accessories / Primary only
	Primary	900 CCA/ 730 CCA AGM/ 800 CCA/ 650 CCA
	Auxiliary	760 CCA/ 200 CCA
		HD high capacity radiator/ HD engine oil cooler / HD transmission fluid cooler /
	Cooling system	police calibrated fan and grille
		Remove key and exit vehicle whole allowing to remain securely idle tosupport
	Police Engine Idle	lights, sirens other on board equipment
Harrie		
Dimensio	ns	
	Fuel Capacity	0 (EV) / 18 - 26 gallons
	GVWR	5990 - 7200 lbs
	Wheelbase	119 - 145 in
	Ground clearance	5.1 - 9.4 in
	Overall Length	198 - 231.7 in
Drivetrain		
	Transmission	8 or 10 speed Select Shift Automatic / lock up torque converter/
	Axle Ratio	3.23 :1 HD limited slip differential /
	Transfer case	AWD / Rear wheel drive /4WD
Chassia		
Chassis	Stooring	Electric newer assisted rack and ninen
	Steering	Electric power assisted rack and pinon
	Suspension	Police durability cycle tested / premium hubs and bearings
		Independent double A-arm with coil over shockand stabilizer bar / Short and
		long arm independent, gas charged twin tube coil over shocks/ heavy duty
	Front	stabilizer bar /Helical coil springs
		Independent double multi-link with coil over shock and stabilizer bar /twin
		tube shocks including load leveling/ aluminumlower contorl arm /independent
	Rear	tension and camber links
	Under body	HD deflector plate
		Steel Wheels / S (120 mph) or V (150 mph) Speed rated tires / Tire pressure
	Wheel & Tires	monitoring system sensor
		Heavy duty 4 wheel anti lock/ Power with dual piston calipers front, single
		piston calipers rear, 4 circuit, ABS /4 wheel long wear-life vented disc / large
		swept area calipers/ ABS electronically controlled brake boost / severd duty
		pads and calipers /Brembo brakes and cooling system / Auto Emergency
	Brakes	Braking Systems unique police temporary disable switch

ATTACHMENT A (CONTINUED)

	1000		Average Guidelines
			Average data mes
Interior			
	Doors		HD door tethers strengthen hinge action
			Hidden rear door lock plunges
		<u> </u>	Simplified rear door panels (no pockets/cupholders)
		1	Wide opening rear doors
	1		Level III & IV NIJ Ballistic Panels
	Seats		Police grade heavy duty cloth front seats /rear vinyl no cost option
		Front	Steel intrusion plates in seat backing
		Rear	Split 60/40 bench /
	Measurements		
		Headroom	Front: 38.6 - 42.3 in / Rear: 36.6 - 40.4
		Legroom	Front: 40.3 - 44.5 in / Rear: 38.1 - 43.4
		Shoulder	Front: 41.8 - 66.0 in / Rear: 50.4 - 65.5
		Hip Room	Front: 55.4 - 62.5 in / Rear: 53.2 - 62.6
	Interior Volume		
		Front	54 - 79.9 cu ft
		Rear	47 - 65.6 cu ft
		Combination	101 - 129.8 cu ft
		Trunk / MAX Cargo	29.7 - 62.9 cu ft
Other			
	Police perimeter a	lert monitors	
	12.1 Intergrated Co		
	Remappable latchi	ed steering wheel	
	Interior tailored po		
	Lockable cargo area vault Simplified fleet keyed- alike fobs		
	Wiring Harness and	d connection gromme	ets throughout vehicle
	HD recovery hooks	built into Class III tra	ailer hitch receiver
Manufact	urer Heavy Duty eva	luations	
	75 mph rear-impac	ct crash test	
	45 mph 6-inch curb	impact test	
	8- inch curb impact	t test	
	Reverse J turns	The contract of the contract o	
	Median crossings		
	30-mph railroad cro		
	15 mph water ford	ing conducted to leve	els of 18"
	40 mph water ford	ing conducted to levl	s of 10"